

# Head Injury Prediction for NASA's Integrated Medical Model

A. S. Weaver<sup>1</sup>, A. E. Zakrajsek<sup>2</sup>, B. E. Lewandowski<sup>1</sup>,  
J. E. Brooker<sup>1</sup>, and J. G. Myers<sup>1</sup>

<sup>1</sup>NASA Glenn Research Center, Cleveland, OH

<sup>2</sup>Purdue University, West Lafayette, IN


HRP Investigators' Workshop

Houston, TX

February 14, 2012



# Integrated Medical Model (IMM)



- Probability and consequences of medical risks
- Integrate best evidence in a quantifiable assessment of risk
- Identify medical resources necessary to optimize health and mission success

# Probabilistic Modeling

- Why computational modeling?
  - Event has not happened during space flight
    - No incidence rate
    - Many unknowns
- The Head Injury Module examines the likelihood of neurologic injury due to head impacts during standardized ISS increments to crewmembers during IVA activities.

# Probabilistic Modeling Overview

- Construct a computational model
  - Define the initiating event scenario and resulting injury
  - Determine available data and develop parameter distributions
  - Mathematically model the physiological response
  - Perform Verification and Validation
  - Relate the physiological response to probability of injury
  - Determine probability of occurrence
- Use probabilistic risk assessment methodology
  - Monte Carlo simulations
  - Estimate the most likely probability and confidence intervals


# Head Injury Mission Scenario

- Head impacts onboard the ISS
- Impact through the center of gravity
- Crewmember without a helmet
- Impacting structure is modeled as a fixed, rigid body




# Injury Definition

- Moderate neurological injury
- Anterograde amnesia of 30 min - 24 hrs
- Abbreviated Injury Scale (AIS) score of three and above



# Lumped Parameter Mathematical Model


- A model of head acceleration response developed in [1] was modified for the ISS head impact scenario
- Allows for both head translation and rotation
- Stiffness and damping relationships taken from [2]



[1] Deb and Ali, 2004  
[2] Sulzer et. al., 2006



# Lumped Parameter Mathematical Model



- The Head Injury Criteria (HIC) score was used to determine risk of injury.
- The relation of HIC to moderate head injury risk was developed from [3].
- The 5<sup>th</sup>-95<sup>th</sup> percentile uncertainty bands were used to define the injury corridor.

[3] Marjoux et. al., 2008



# Input Distributions

- Head mass
- Head radius
- Moment of inertia
- Neck stiffness
- Impact velocity
- Incidence rate
- Probability of injury coefficients

# Assumptions on Incidence Rate


- Data from Scheuring et. al. (2009) were used to develop a distribution for the event that an crew member hits his/her head.
- There were 9 total head injuries reported.
  - Created a distribution using only injuries from translation, impacts, and unknown categories



# Assumptions on Velocity at Impact

- Velocities are given in NASA-STD-3000 as
  - 0.15-0.30 m/s for moving equipment
  - 0.40-0.60 m/s for translation
  - 1.8 m/s for “gymnastics”
- Percentages and bounds were constructed using injuries from transferring equipment, stowing equipment, translating, impacting structures, and unknown.


# Model Validation



- The output of the current model was compared to data from a head-drop test [2]
  - Model showed a +1.2% error in peak acceleration and -1.0% error in HIC score when compared to experimental data.

# Results of Monte Carlo Simulation

	Mean	Standard Deviation	5 <sup>th</sup> Percentile	95 <sup>th</sup> Percentile
Probability of Moderate Neurological Injury per six months (per year)	$1.16 \times 10^{-4}$ ( $2.32 \times 10^{-4}$ )	$5.48 \times 10^{-4}$ ( $1.10 \times 10^{-3}$ )	$3.26 \times 10^{-7}$ ( $6.52 \times 10^{-7}$ )	$4.94 \times 10^{-4}$ ( $9.88 \times 10^{-4}$ )



# Sensitivity Analysis

- Percentage that each input variable accounts for the variability in the probability of injury output

Input Parameter	% Contribution to Variance
Impact Velocity	64.80
Injury Coefficient, b	23.58
Incidence Rate	10.66
Head Mass	0.94
Injury Coefficient, a	0.01
Moment of Inertia	0.00
Neck Stiffness	0.00

# Assumptions and Limitations

- Minor injuries that may require med kit items, are not covered by this model.
- HIC score does not take rotation into account. Therefore, in order to obtain a more conservative result, only translation was considered.
- The headform impact model, which is used by the automobile industry to examine the effectiveness of countermeasures is assumed to accurately represent head impact onboard the ISS.



# Thank You

## Acknowledgements

- DeVon Griffin
- Eric Milo
- Michael McRae
- Elise Griffin

## References

- [1] Deb A, Ali T. International Journal of Impact Engineering 2004;30: 521-539.
- [2] Sulzer J et. al. SAE International Conference on Digital Human Modeling. Lyon, France; 2006.
- [3] Marjoux D et. al. Accident Analysis & Prevention 2008;40: 1135-1148.

